

Main Specifications

▼Size

2.5" 4"

▼Installation type

Bottom mount (A) /
 Bottom mount with flange (B) /
 Back mount (centric thread)
 (ADC) /
 Back mount with flange
 (centric thread) (BDC) /
 Back flange with flange
 (eccentric thread) (BDE)

▼Window

PC / Glass
 O-ring sealed / PE gasket

▼Process connection

Material:
 Copper / Stainless steel
 Thread size: 1/8" , 1/4" ,
 3/8" , 1/2"

Thread spec.: BSPT / NPT / PF

▼Ambient temperature

-20°C to +60°C

▼Fluid temperature

+60°C (Copper alloy type)
 +100°C (Stainless steel type)

▼Protection level

IP54 for dry type (Standard) /
 IP65 for liquid-filled type
 (Option)

Other Specifications

▼Ring

Stainless steel

▼Pointer

Aluminum with black enamel

▼Peak hold pointer

Aluminum with black enamel /
 Red plastic

▼Measuring elements

Bourdon tube

Material:

Copper / Stainless steel

▼Accuracy

Standard: ±1.6%

Option: ±1%

Pressure Gauge with Peak Hold Pointer Model: PHPG








Features

- Record peak pressure value
- IP54 for dry type (Standard) /
IP65 for liquid-filled type (Option)

Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales.
 (If there is any change on specification, please take the latest version as standard.)



Installation type

				
A	B	ADC	BDC	BDE

How to order

<u>PHPG</u>		<u>EPG</u>		<u>O</u>	<u>A</u>	<u>2.5"</u>	<u>1/4"</u>	<u>PT</u>	<u>0 to 20 bar</u>
Model	code	Type	code	Liquid-filling	Installation type	Size	Thread size	Thread type	Pressure range
PHPG	SC	Stainless steel	O	Dry	A	2.5"	1/8"	PT	-1...0 bar
	SUS	All stainless steel	L	Glycerin	B	4"	1/4"	NPT	-1...+1 to +20 bar
			S	Silicone	ADC	3/8"	PF	0...1 to 1000 bar	
					BDC				
					BDE	1/2"		Others	

Order example: PHPG-SC-O-A-2.5" -1/4" -PT-0 to 20 bar