

Main specification	Other specification
<p>▼Dimension 300 x 300 x 150 mm</p> <p>▼Thread size Material: SS316 1/4" , 1/2"</p> <p>▼Thread type BSPT, NPT, PF</p> <p>▼Pressure range Min: -0.95bar Max: 60 bar</p> <p>▼Adjustment resolution 0.1mbar</p> <p>▼Medium Air</p>	<p>▼Body materials Stainless steel, aluminum alloy</p> <p>▼Sealing materials Buna-N</p> <p>▼Pressurize operation Manual</p> <p>▼Weight 10kg</p> <p>▼Accessory Sealing components x 10 Switch valve sealing ring x 4</p>

Desk-top Pneumatic Pressure Calibration Pump

Model: DH/VCP200E

Introduction

Apply to calibrating pressure gauges, transmitters, sensors and other pressure instruments



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- Portable design
- Made up of top quality stainless steel and aluminum materials and with advanced German sealing technology and components
- The medium of pressure transmission is clean air, increasing the accuracy when calibrating instruments
- Smoothly switch between positive and negative (vacuum) pressure
- The open structure enabling easy to clean and maintain
- Fine adjustment resolution 0.1 mbar

How to order

DH/VCP200E Desk-top Pneumatic Pressure Calibration Pump									
Std.	Spec.	Code	Item	Code	Item	Code	Item	Code	Item
A	Thread size	2	1/4"	4	1/2"	-	-	-	-
2N	Thread type	P	BSPT	N	NPT	F	PF	-	-
/B	Other requests	/A	Third party notarized document						
		/B	Inspection report (issued by Re-Atlantis)						
		/C	Tag						

Order example: DH/VCP200E - A - 2N - /B