ATLANTIS

Main Specifications

▼ Size 4.5" (120mm) ▼Installation type Bottom mount ▼ Pressure connection Material: SS316 M20x1.5 Other thread spec. are available made-to-order ▼ Pressure range Gauge**▼** 0...10kPa to 600bar Negative pressure ▼ -760 to 0mmHg ▼Applicable media Liquid and gas that compatible with SS316 ▼Ambient temperature 0 to 50°C Ambient humidity <95%RH Atmospheric pressure 86-106kPa

Other Specifications

- ▼ Screen display 5-digit LCD display with blue backlight Display range▼ -99999~99999 **Resolution**▼ 0.0001 ▼Refresh rate
- 4 times/sec. Power supply
- AA battery x3
- ▼ Pressure unit

MPa, bar, kg/cm², mmH₂O, mmHg, psi

- ▼Accuracy
- ±0.1% F.S. (standard) ±0.05% F.S. (options)
- ▼Weight

800a ▼Other requests (Option)

Third party notarized documents Inspection report Tag Customized dial (Brand, scale, etc.) Thread adapter: adapt to other threads RS485 output

Dimension (unit: mm)



High Accuracy Digital Pressure Gauge Model: DPG-0.05B4.5 (5CD) Introduction

DPG-0.05B4.5 (5CD) high precision digital pressure gauge adopts imported precision pressure sensor and internal precision temperature compensation sensor, with accuracy up to 0.05%F.S. and excellent stability. DPG-0.05B4.5 (5CD) an be used as standard calibrating digital pressure gauges, and also can be applied to pressure field display in chemical, hydraulic, petroleum and other industrial environments.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- Accuracy 0.05%F.S.
- Fully functional and easy to operate
- 5-digit LCD display with blue backlight, suitable for reading in dark
- One key to zero design
- The decimal places can be set by user
- Multiple pressure unit switching
- With current remaining power indication
- RS485 digital output (option)

How to order

DPG-0.0	5B4.5 (5CD)	High	Accuracy Digit	al Press	ure Gauge				
Std.	Spec.	Code	ltem	Code	ltem	Code	ltem	Code	ltem
2N	Pressure connection	2N	1/4″ NPT	0	Others	-	_	-	-
Custom	Pressure	Gauge : 0…10kPa to 600bar							
	range	Negative	egative pressure : -760 to 0mmHg						
01	Accuracy	01	±0.1%F.S.	005	±0.05%F.S.	-	-	—	-
/B		/A	Third party notarized document						
		/B	Inspection report (issued by Re-Atlantis)						
	Other	/C							
	requests	/D							
		/E	Thread adapter: adapt to other threads						
		/F	RS485 output						

Order example: <u>DPG-0.05B45(5CD)</u> - <u>2N</u> - <u>(0-500bar)</u> - <u>01</u> - <u>/B</u>