ATLANTIS

Main Specifications

▼ Size

3″ (83mm) ▼Installation type Bottom mount ▼Pressure connection Material: stainless steel 1/4″ NPT Other thread spec. are available made-to-order

▼ Pressure range

Gauge pressure ▼ 0...200kPa to 35MPa Negative pressure ▼ -30 to 0inHg

▼Applicable fluid

Liquid and gas that compatible with stainless steel

▼Ambient temperature 0-50℃

▼Ambient humidity <95%RH

▼Atmospheric pressure 86-106kPa

Other Specifications

▼Case Stainless steel

- ▼Screen display
- 5-digit LCD display with backlight Display range▼
- -99999~99999 Resolution ▼

0.0001

▼Screen size 53 (W) x 28 (H)mm

▼Value refresh rate

- 1~10 times/sec.
- Power supply

AAA battery x3

▼ Pressure unit bar kg/cm², kPa, MPa, ftH₂O, mbar, inH₂O, inHg, mmHg, psi

▼Accuracy

±0.5% F.S. (standard) ±0.25% F.S. (options)

▼Weight

500g ▼Other requests (Option)

Third party notarized documents Inspection report Tag Customized dial (Brand, color, etc.) Thread adapter: Adapt other type of thread 4-20mA signal output-Switch signal output RS485 output

Multifunction Digital Pressure Gauge Model: DPG-0.25B3.0 (5CD) Introduction

DPG-0.25B3.0 (5CD) multifunction digital pressure gauges features integrated stainless steel design, complete functions, and high measuring accuracy. Suitable for a variety of industrial pressure testing requirements.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- Accuracy: 0.25%F.S.
- **5**-digit LCD display with backlight
- Switchable pressure unit
- Switchable max./min. pressure value display
- With current remaining battery indicator
- Refresh rate, auto off time, and backlight auto off time can be adjusted
- 4-20ma output, switch signal output, RS485 output performance are available (Option)

How to order

DPG-0.25B3.0 (5CD) Multifunction Digital Pressure Gauge									
Std.	Spec.	Code	ltem	Code	ltem	Code	ltem	Code	ltem
2N	Pressure connection	2N	1/4″ NPT	0	Others	-	-	-	_
Custom	Pressure	Gauge pressure: 0···200kPa to 35MPa							
custom	range	Negative pressure: -30 to 0inHg							
05	Accuracy	05	±0.5% F.S.	025	±0.25% F.S.	—	_	-	_
/В		/A	Third party notarized document						
		/B	Inspection report (issued by Re-Atlantis)						
		/C	Tag						
	Other	/D	Customized dial (Brand, color, etc.)						
	requests	/E	Thread adapter: Adapt other type of thread						
		/F	4-20mA signal output						
		/	Switch signal output						
		/H	RS485 output						
Order example: <u>DPG-0.25B30(5CD)</u> - <u>2N</u> - <u>(0~30MPa)</u> - <u>05</u> - <u>/B</u>									