

Main Specifications	Other Specifications
▼ Size 4.5"	▼ Ring Aluminum alloy
▼ Pressure connection Material: SS316 Laser welding 1/4" PT 1/2" PT Other thread type available upon request	▼ Case ABS
▼ Pressure range -0.1~60 MPa	▼ Screen display 6-digit LCD with blue backlight Progress bar for current pressure indication Current temperature display
▼ Applicable fluid Liquid and gas that compatible with SS 316L / Pure, non-corrosive gas	▼ Screen size 66 (W) x 47 (H) mm
▼ Ambient temperature -10°C~50°C	▼ Refresh rate 3 times/sec (default) 10 times/sec, 1 times/sec
▼ Ambient humidity < 95% R.H.	▼ Pressure unit Pa, kPa, MPa, psi, bar, mbar, kgf/cm ² , mmH ₂ O, mmHg
▼ Atmospheric pressure 860...1060 mbar	▼ Resolution 0.0001
▼ Temperature error Standard temp.: 20°C Max. error: ±0.1%F.S. (@0~50°C)	▼ Measuring elements High-tech silicon wafer SS 316L diaphragm
▼ Power supply Include DC 8.4V charger	▼ Accuracy Pressure: ±0.025%F.S. / ±0.05%F.S. / ±0.1%F.S. / ±0.2%F.S. / ±0.5%F.S. Temperature: ±2°C
▼ Operating pressure Overpressure: 1.2* full scale Burst pressure: 1.3* full scale	▼ Communication port (option) RS232
▼ Weight 500g	▼ OEM service


Digital Precision Pressure Gauge
Model: DPG-H4.5RS
Introduction
DPG-H4.5RS digital precision pressure gauge adopt high/low aging & temperature compensation technology to ensure its accuracy and stability. DPG-H4.5RS is suitable in field calibration for precision/general pressure gauge & sphygmomanometer.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- Accuracy up to 0.025%
- 6-digit LCD display with blue backlight
- Large screen size 66 x 47mm
- Switchable 9 pressure units
- Current temperature display
- Zero / Span calibration
- Overpressure alarm – Peak pressure and min pressure monitor
- RS232 communication port (option)



How to order

DPG-H4.5RS Digital Precision Pressure Gauge										
Std.	Spec.	Code	Item	Code	Item	Code	Item	Code	Item	
2P	Process connection	2P	1/4" PT	4P	1/2" PT	0	Others	-	-	
Custom	Pressure range	-0.1~60 MPa								
03	Accuracy	01	±0.025%F.S.	02	±0.05%F.S.	03	±0.1%F.S.	04	±0.2%F.S.	
		05	±0.5%F.S.	-	-	-	-	-	-	
/B	Other requests	/A	Third party notarized document							
		/B	Inspection report (issued by Re-Atlantis)							
		/C	Tag							
		/D	Differential pressure type							
		/E	Install a diaphragm seal							
		/F	Thread adapter							
		/G	Connection material – SS 316L							
		/H	RS232 communication (minimum order 30 pcs)							
		/I	Silicone rubber protection case							
		/J	Overpressure alarm buzzer							

Order example: DPG-H4.5RS - 2P - (0~20MPa) - 03 - /B