Main Specifications

▼Size

3"

▼Installation type

Bottom mount

▼Pressure connection

Material: stainless steel

1/4" PT

1/4" NPT

Other thread type can be customized upon request

▼Pressure range

Gauge pressure ▼

0~1000 bar

Vacuum **▼**

-760mmHg...0

▼Applicable media

Liquid and gas that compatible with stainless steel

▼Operating temperature

-15 to 70°C

▼Media temperature

+80°C

Other Specifications

▼Case material

PVC / Stainless steel

▼Screen display

4-digit LCD display with

backlight function

▼Screen size

Plastic case:

41 (W) x 16 (H) mm

Stainless steel case:

41 (W) x 16 (H) mm

▼Switchable unit

Gauge pressure:

MPa, psi, kg/cm²

Vacuum: mbar; mmHg, inHg

▼Power supply

Plastic case: 1.5V battery×3 Stainless steel case: 9V lithium battery x1

▼Accuracy

±1.0% F.S. /

±0.5%F.S.

▼Max. operating pressure

150% F.S.



Model: DPG-K3.0



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- 4-digit LCD screen display with blue backlight ensures clear reading in the dark place
- Plastic / Stainless steel case available
- Power saving mode auto turn off backlight after 10 secs
- Calibration mode reset pressure reading to zero when screen display effected by ambient temperature

How to order

DPG-K3.0 3" Digital Pressure Gauge										
Std.	Spec.	Code	ltem	Code	ltem	Code	ltem	Code	ltem	
PVC	Case material	PVC	PVC	SS	Stainless steel	1	-	-	-	
2P	Pressure connection	2P	1/4" PT	2N	1/4" NPT	0	Others	_	-	
Custom	Pressure range	-/60mmHq···0···1000 bar								
10	Accuracy	05	±0.5%F.S.	10	±1.0% F.S.	_	_	_	-	
						•		•		
/B	Other requests	/A	Third party notarized document							
		/B	Inspection report (issued by Re-Atlantis)							
		/C	Tag							

Order example: DPG-K3.0 - PVC - 2P - (0~10bar) - 10 - /B