

Main Specifications	Other Specifications
<p>▼ Size 4"</p> <p>▼ Installation type Bottom mount (A)</p> <p>▼ Window PC / Glass</p> <p>▼ Thread size Material: copper alloy 3/8" PT 1/4" PT Other thread specs are available upon request</p> <p>▼ Pressure range 0...2 ~ 28bar</p> <p>▼ Applicable fluid Liquid and gas that compatible with copper alloy</p> <p>▼ Ambient temperature -40°C ~ +60°C</p> <p>▼ Fluid temperature +60°C</p> <p>▼ Temperature error Every 12°C max. error±0.3% F.S</p> <p>▼ Protection level IP43</p>	<p>▼ Ring Steel with black enamel</p> <p>▼ Ring mount Screw fixed</p> <p>▼ Case Steel with black enamel</p> <p>▼ Pointer Aluminum with black enamel</p> <p>▼ Dial face Adjustable screw on dial face Pressure unit, scale, and color can be customized upon request</p> <p>▼ Measuring elements Bourdon tube Material: copper alloy</p> <p>▼ Movement Copper alloy</p> <p>▼ Accuracy ±2.5% (Option: ±1.6%)</p> <p>▼ Operating pressure Stabilization 3/4* full scale Fluctuation 2/3* full scale Impulse 1* full scale</p>

4" Black Steel Case Pressure Gauge (Zero Adjustment Type)

Model: ZPG-4

Introduction

ZPG black steel case pressure gauge with zero adjustment function is applicable to general engineering or environment required field pointer calibration.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- Special 4" black steel case pressure gauge designed for engineering application
- Adjustable screw for field pointer calibration / zero adjustment

How to order

ZPG-4 4" Black Steel Case Pressure Gauge (Zero Adjustment Type)									
Std.	Spec.	Code	Item	Code	Item	Code	Item	Code	Item
B	Connection material	B	Copper alloy	O	Others	–	–	–	–
B	Bourdon tube material	B	Copper alloy	O	Others	–	–	–	–
2	Thread size	2	1/4"	3	3/8"	O	Others	–	–
P	Thread type	P	PT	O	Others	–	–	–	–
Custom	Pressure range	0...2 to 28bar Pressure unit (psi, bar, kPa, kg/cm2, MPa, inHg, mmHg, cmHg, etc...) & single / dual scale can be customized upon request							
B	Accuracy	A	±1.6%	B	±2.5%	–	–	–	–
/D	Other requests	/A	Third party notarized documents			/B	Inspection report		
		/C	Tag			/D	Customized dial face (scale, color, unit, etc.)		
		/E	Adjustable pointer			/F	Epoxy coating		
		/G	Chrome-plated thread			–	–		

Order example: ZPG-4 - B - B - 2 - P - (0...10bar) - B + /D